





REV	DESCRIPTION	DATE



NOTE:

- MATERIAL AND FINISH  
 HOUSING:HIGH-TEMP. THERMOPLASTIC. UL 94V-0.  
 ACTUATOR:HIGH-TEMP. THERMOPLASTIC. UL 94V-0.  
 CONTACT:PHOSPHOR BRONZE.  
 PLATING:TIN OR GOLD PLATED OVER NICKEL.  
 HOLDDOWN:BRASS. PLATING:TIN PLATED OVER NICKEL.
- ELECTRICAL  
 CURRENT:0.5A MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE:250V AC MIN.  
 CONTACT RESISTANCE:30mΩ MAX.  
 INSULATION RESISTANCE:100MΩ MIN.
- ENVIRONMENTAL  
 TEMPERATURE:-25°C TO +85°C
- PART NO.  
 CNT-FPC050-XX-TDM-S21-230

RECOMMENDED PCB LAYOUT

<p><b>CNT</b> 肯耐特电子有限公司</p>				GENERAL TOLERANCE		DRAWN 董道丽	DATE 20191011	DWG. NO.	TITLE
				X.° ±5°	X. ±0.30	CHECK 王芳芳	DATE 20191011	PART. NO.	
REV. 1.0	UNIT mm	SCALE 1:1		.X° ±3°	.X ±0.38	APPROVE 王元中	DATE 20191011	CNT-FPC050-XX-TDM-S21-230	FPC 0.5 PITCH ZIF LOCK LOWER CONTACT FOR SMT90° TYPE
				.XX° ±2°	.XX ±0.25				
				.XXX° ±1°	.XXX ±0.15				